PUBLIC TRANSPORT AUTHORITY

SAFEWORKING RULES AND PROCEDURES

6003 BLOCKING FACILITIES

6003 Blocking Facilities Rev1.00

Date: 01 November 15

Page 1 of 4

9100-000-007 Safeworking Rules and Procedures

CONTENTS

1.	Purpose	. 3
	General	
	Management of Blocking Facilities	
	3.1. Temporary Removal	
	3.2. Permanent Removal	. 4
4.	Keeping Records	. 4
5.	Reference	. 4
6	Effective Date	/

1. PURPOSE

The purpose of this rule is to detail the protocols for using *Blocking Facilities* in the Public Transport Authority (PTA) *Network*. These devices are used to prevent the unintended *Issue* of *Occupancy Authorities* or the operation of *Signals* or *Point* equipment.

2. GENERAL



WARNING

Unless assured by the *Train Controller*, *Competent Workers* must not assume that:

- Signals have been set at Stop;
- Points have been correctly set; or
- Blocking Facilities have been applied.

Unless otherwise permitted in the PTA Safeworking Rules and Procedures:

- equipment with Blocking Facilities applied must not be operated; and
- Train Controllers must not issue Occupancy Authorities for Sections that are shown as Blocked out of use on Train Control Diagrams.

3. MANAGEMENT OF BLOCKING FACILITIES

Before applying *Blocking Facilities* to *Signals, Points* or *Sections* of *Track, Train Controllers* must make sure that any affected *Points* are set in the correct positions.

3.1. TEMPORARY REMOVAL

Blocking Facilities may be temporarily removed from controls, with the approval of the Competent Worker who requested the application of the Blocking, in order to:

- set a different Route using the same controls;
- after safe arrangements have been made to clear a Signal to permit a movement over the blocked Route; or
- maintain and test the Signalling equipment.

Train Controllers must restore Blocking Facilities as soon as the activity that required their temporary removal has been completed, and confirm that the Blocking has been reapplied with the Competent Worker who requested the Blocking.

3.2. PERMANENT REMOVAL

Blocking Facilities must be removed from controls when the conditions that required their application no longer exist and with the approval of the Competent Worker who requested the Blocking.

4. KEEPING RECORDS

Train Controllers and the Competent Worker requesting the Blocking must make a Permanent Record of the application and removal of Blocking Facilities.

5. REFERENCE

Nil

6. EFFECTIVE DATE

1 November 2015

6003 Blocking Facilities Rev1.00
Date: 01 November 15